





600W PURE SINE WAVE DC TO AC POWER INVERTER

Model	P600-121	P600-122	P600-241	P600-242	P600-481	P600-482
Rated power	600W					
Surge power	1200W(Few seconds)					
Output voltage	110V	230V	110V	230V	110V	230V
Output frequency	50/60Hz ± 3					
No load current draw	≤ 0.7A					
Output waveform	Pure Sine Wave 					
LED Indicator	Green-power on, red-failure & protection					
Protection function	Bat. low voltage alarm & shut down, over temperature, over voltage, short circuit, reverse polarity, earth leakage, overload					
Input voltage	12V	24V	24V		48V	
Replaceable fuse	40A × 2		20A × 2		10A × 2	
Cooling fan	By load control					
Dimension	26 × 15 × 7.77cm (L × W × H)					
N.W./Unit	2030g					
QTY/Ctn	6pcs					
Meas./Ctn	57 × 30.5 × 30cm					
Packing	Gift box					
Certification	CE-EMC/LVD, RoHS, E-mark					

1000W PURE SINE WAVE DC TO AC POWER INVERTER

Model	P1000-121	P1000-122	P1000-241	P1000-242	P1000-481	P1000-482
Rated power	1000W					
Surge power	2000W(Few seconds)					
Output voltage	110V	230V	110V	230V	110V	230V
Output frequency	50/60Hz ± 3					
No load current draw	≤ 0.8A					
Output waveform	Pure Sine Wave 					
LED Indicator	Green-power on, red-failure & protection					
Protection function	Bat. low voltage alarm & shut down, over temperature, over voltage, short circuit, reverse polarity, earth leakage, overload					
Input voltage	12V	24V	24V		48V	
Replaceable fuse	30A × 4		15A × 4		10A × 4	
Cooling fan	By load control					
Dimension	29.3 × 15 × 9.75cm (L × W × H)					
N.W./Unit	2900g					
QTY/Ctn	4pcs					
Meas./Ctn	38.5 × 35 × 34cm					
Packing	Gift box					
Certification	CE-EMC/LVD, RoHS, E-mark					

