

ISO9001:2008 RoHS -LVD/EMC

### 1500W PURE SINE WAVE DC TO AC POWER INVERTER



Model	P1500U-121	P1500U-122	P1500U-241	P1500U-242	P1500-481	P1500-482
Rated power	1500W					
Surge power	3000W(Few seconds)					
Output voltage	110V	230V	110V	230V	110V	230V
Output frequency	50/60Hz ± 3					
No load current draw	≤ 1A					
Output waveform	Pure Sine Wave					
USB port	5V, 500mA(Optional)			For 48V input, No USB		
Remote control	Optional					
Protection function	Bat. low voltage alarm & shut down, over temperature, over voltage, short circuit, reverse polarity, earth leakage, overload					
Input voltage	12V		24V		48V	
Replaceable fuse	30A × 6		15A × 6		7.5A × 6	
Cooling fan	By load control					
Dimension	34.5 × 23 × 10.8cm (L × W × H)					
N.W./Unit	4700g					
QTY/Ctn	2pcs					
Meas./Ctn	40 × 31.5 × 38cm					
Packing	Gift box					
Certification	CE-EMC/LVD, RoHS, E-mark					

Note: if without USB, the model is P1500

### 2000W PURE SINE WAVE DC TO AC POWER INVERTER

Model	P2000U-121	P2000U-122	P2000U-241	P2000U-242	P2000-481	P2000-482
Rated power	2000W					
Surge power	4000W(Few seconds)					
Output voltage	110V	230V	110V	230V	110V	230V
Output frequency	50/60Hz ± 3					
No load current draw	≤ 1.2A					
Output waveform	Pure Sine Wave					
USB port	5V, 500mA(Optional)			For 48V input, No USB		
Remote control	Optional					
Protection function	Bat. low voltage alarm & shut down, over temperature, over voltage, short circuit, reverse polarity, earth leakage, overload					
Input voltage	12V		24V		48V	
Replaceable fuse	30A × 8		15A × 8		7.5A × 8	
Cooling fan	By load control					
Dimension	34.5 × 23 × 10.8cm (L × W × H)					
N.W./Unit	4850g					
QTY/Ctn	2pcs					
Meas./Ctn	40 × 31.5 × 38cm					
Packing	Gift box					
Certification	CE-EMC/LVD, RoHS, E-mark					



Note: if without USB, the model is P2000