

Features

- Conform to IEC 60439
- Main incoming options with RCCB or Isolator & RCCB + Isolator or MCB
- Copper tin-plated coated busbar, fully shrouded, rated 150AMP
- Neutral and Earth bars are mounted on separate insulator
- Supplied with hinged outer door, and removable screwed inside door



TPN Non Split Din Rail Distribution Boards

- Three phase 415V 50Hz AC Supply.

Busbar Rating	No. of Ways	Incomer Isolator	Incomer 300mA 30mA		Catalog Number	Dimensions(mm)		
						Width mm	Height mm	Depth mm
150A	2	100A	63A	63A	HPE4-02150	320	355	85
150A	4	100A	63A	63A	HPE4-04150	320	355	85
150A	6	100A	63A	63A	HPE4-06150	320	355	85
150A	8	100A	63A	63A	HPE4-08150	320	355	85
150A	10	100A	63A	63A	HPE4-10150	320	355	85
150A	12	100A	63A	63A	HPE4-12150	320	355	85

TPN Split Din Rail Distribution Boards

- Three phase 415V 50Hz AC Supply.



Busbar Rating	NO. Of Ways	Incomer Isolator	Incomer 300mA 30mA		Catalog Number	Dimensions(mm)		
						Width mm	Height mm	Depth mm
150A	2+2W	100A	63A	63A	HPE4-2+2W	400	540	85
150A	4+2W	100A	63A	63A	HPE4-4+2W	400	610	85
150A	4+4W	100A	63A	63A	HPE4-4+4W	400	700	85
150A	6+2W	100A	63A	63A	HPE4-6+2W	400	700	85
150A	6+4W	100A	63A	63A	HPE4-6+4W	400	460	85
150A	6+6W	100A	63A	63A	HPE4-6+6W	400	850	85
150A	8+2W	100A	63A	63A	HPE4-8+2W	400	760	85
150A	8+4W	100A	63A	63A	HPE4-8+4W	400	850	85
150A	8+6W	100A	63A	63A	HPE4-8+6W	400	930	85
150A	8+8W	100A	63A	63A	HPE4-8+8W	400	1000	85
150A	10+2W	100A	63A	63A	HPE4-10+2W	400	850	85
150A	10+4W	100A	63A	63A	HPE4-10+4W	400	930	85
150A	10+6W	100A	63A	63A	HPE4-10+6W	400	1000	85
150A	12+2W	100A	63A	63A	HPE4-12+2W	400	930	85
150A	12+4W	100A	63A	63A	HPE4-12+4W	400	1000	85
150A	12+6W	100A	63A	63A	HPE4-12+6W	400	1080	85
150A	12+8W	100A	63A	63A	HPE4-12+8W	400	1150	85