

Isolator Switches



HPN

Description

HPN isolator is rigidly built to withstand more than just the vagaries of the weather, it is designed also for frequent switching even on severe load such as switching of motor loads or other highly inductive load. Suitable to be mounted in outdoor and indoor for diverse environment.

Features

- ⊙ Switching ON & OFF on-load
- ⊙ Padlockable handle with 7mm hole in OFF position
- ⊙ Dual 25mm threaded conduit entries on top and bottom
- ⊙ IP66 rating prevents from heavy dust and water ingress




Approvals

CB, CE, SAA

Technical Data

- ⊙ Standard: IEC/EN60947-3, AS/NZS 3947
- ⊙ Rated Voltage: 240/415V AC
- ⊙ Rated Frequency: 50/60Hz
- ⊙ Utilization Category: AC22A
- ⊙ Number of Pole: 1, 2, 3 pole
- ⊙ IP Protection: IP66

Specification

Model	Rating(Amps)	Designation	Wiring Diagram	IP Rating
HPN120	20A	single pole		IP66
HPN132	32A			
HPN163	63A			
HPN220	20A	double pole		IP66
HPN232	32A			
HPN263	63A			
HPN320	20A	triple pole		IP66
HPN332	32A			
HPN363	63A			

Outline & Mounting Dimensions

