

Combination Switched Sockets

66SS

Description

Both 66SS and 66CV series combination switched socket are designed and manufactured to many adverse commercial and industrial condition, available from 250V 10A to 500V 63A and all internal connection switches and sockets are pre-wired.
















Approvals

CE, SAA

Technical Data

- Standard: BS1363, AS/NZS 3123
- Rated Voltage: 250/500V AC
- Rated Frequency: 50/60Hz
- Utilization Category: AC22A
- IP Protection: IP55/IP66

Specification

Model	Description	Rating (Amp)	Voltage (V)	No. of Phase	Configuration
66CV313N	BS 3 Pin Switched Socket *	13	250	1	
66CV315RP	BS 3 Pin Switched Socket *	15	250	1	
66SS310	3 Pin Switched Socket	10	250	1	
66SS315	3 Pin Switched Socket	15	250	1	
66SS410	4 Pin Switched Socket	10	500	3	
66SS420	4 Pin Switched Socket	20	500	3	
66SS432	4 Pin Switched Socket	32	500	3	
66SS440	4 Pin Switched Socket	40	500	3	
66SS450	4 Pin Switched Socket	50	500	3	
66SS510	5 Pin Switched Socket	10	500	3	
66SS516	5 Pin Switched Socket	16	500	3	
66SS520	5 Pin Switched Socket	20	500	3	
66SS532	5 Pin Switched Socket	32	500	3	
66SS540	5 Pin Switched Socket	40	500	3	
66SS550	5 Pin Switched Socket	50	500	3	

* N- probuberant flap to enclose BS plug top when plug in

* RP- for round BS plug top

Outline & Mounting Dimensions

