

Rotary Isolator Switches

HPB

Description

HPB series is designed rotary isolator switch especially for frequent switching even on severe load such as switching of motor loads or other highly inductive loads.

Approvals

CB, CE, SAA

Technical Data

- ◎ Standard: IEC/EN 60947-3, AS/NZS 3947
- ◎ Rated Voltage: 500V AC
- ◎ Rated Current: 16A, 20A, 25A, 32A, 40A, 63A, 100A, 125A, 160A
- ◎ Rated Frequency: 50/60Hz
- ◎ Utilization Category: AC22A/AC23A
- ◎ IP Protection: IP66

Specification

Model	Rating (Amps)	Rated operational current Ie AC23A, AC3			Rated operational power AC23A(for motor)			Dimension (Lx W x H)
		415V	500V	660V	415V	500V	660V	
HPB316	16A	16A	16A	16A	7.5kw	7.5kw	11kw	100 x 80 x 105
HPB320	20A	20A	20A	20A	7.5kw	7.5kw	11kw	
HPB325	25A	25A	25A	25A	7.5kw	7.5kw	11kw	
HPB332	32A	32A	32A	25A	11kw	11kw	11kw	125 x 100 x 120
HPB340	40A	40A	40A	25A	11kw	15kw	18.5kw	
HPB363	63A	63A	63A	50A	18.5kw	22kw	25kw	116 x 156 x 140
HPB3100	100A	100A	80A	63A	37kw	37kw	30kw	
HPB3125	125A	125A	80A	63A	37kw	37kw	30kw	150 x 216 x 140
HPB3160	160A	160A	100A	80A	37kw	37kw	30kw	
HPB416	16A	16A	16A	16A	7.5kw	7.5kw	11kw	100 x 80 x 105
HPB420	20A	20A	20A	20A	7.5kw	7.5kw	11kw	
HPB425	25A	25A	25A	25A	7.5kw	7.5kw	11kw	125 x 100 x 120
HPB432	32A	32A	32A	25A	11kw	11kw	11kw	



Outline & Mounting Dimensions

